

ALT ☐ I ☐ II ☐ III Approved by: \_\_\_\_\_ Date: \_\_\_\_\_



Form	ACO1 - Well Completion
Operator	Colt Energy Inc
Well Name	JOHNSON, D 30
Doc ID	1678716

#### Casing

Purpose Of String	Size Hole Drilled	Size Casing Set	Weight	Setting Depth	Type Of Cement	Number of Sacks Used	Type and Percent Additives
Surface	11.25	8.625	24	20	Portland	8	None
Production	4.5	4.5	11.6	1027	Thick Set (OWC)	125	2 #/sx Phenoseal



**ELITE**  
CEMENTING & ACID SERVICE, LLC

Camp Eureka

Remarks: Safety Meeting: Rig up to 4 1/2" casing. Break circulation w/ 5 Bbl fresh water, Pump 500<sup>gal</sup> Flush w/ 80<sup>gal</sup> H<sub>2</sub>O, 10 Bbl water spacer @ 7BPM. Mixed 125 sks Thick Set Cement w/ 2<sup>gal</sup> Phenaseal/sk @ 13.6<sup>gal</sup>/sk, yield  $\approx .71 = 38$  Bbl slurry. Wash out pump & lines. Shut down. Release plug. Displace plug to seat w/ 16 1/2 Bbl fresh water. Final pumping pressure of 900 PSI. Bump plug to 1400 PSI. Wait 2 mins. Release pressure. Float held. Close casing in w/ 0 PSI. Good cement returns to surface = 5 1/2 Bbl slurry to pit. Annulus standing full of cement. Job complete. Rig down.

[illegible]

Title Co/Rep.

I agree to the payment terms and conditions of services provided on the back of this job ticket. Any amendments to payment terms must be in writing on the front of this job ticket or in the Customer's records at ELITE's office.



Colt Energy Driller's Log													
Lease: Johnson, D			Well No. 30		Well Location: 1639' FSL & 1703' FWL			Sec. 11		Twp. 24S		Rng. 18E	
API #: 15-001-31748			Type: Oil		County: AL			State: KS		Spud Date: 12/6/2022		Total Depth: 1037'	
Driller: Pat Stewart			Surface Casing		Bit Record				Coring Record				
Crew: Dan Foust			Bit Size:	11.25"	Type	Size	Start	End	Core #	Size	Start	End	
Jake Benedict			Casing Size:	8.625"	PDC	11.25"	0	20'	1				
Start Rig Hrs: 21270			Casing Length:	20'	PDC	6.75"	20'	1037'	2				
End Rig Hrs: 21300			Cement used:	8 sx					3				
Total Rig Hrs: 30			Cement Type:	Portland					4				
From	To	Formation			From	To	Formation			Pipe Tally			
0	17	Overburden								1	41.10	19	39.40
17	80	Shale								2	41.10	20	42.10
80	160	Limestone								3	41.20	21	41.10
160	208	Shale								4	35.00	22	41.10
208	329	KC Limestone								5	40.80	23	41.00
329	534	Shale								6	44.60	24	40.80
534	541	Limestone								7	41.10	25	41.00
541	592	Shale								8	40.90	26	
592	610	Limestone								9	40.80	27	
610	645	Shale								10	41.10	28	
645	670	Limestone								11	41.00	29	
670	945	Shale								12	41.10	30	
945	950	Sandstone								13	40.80	31	
950	1000	Shale								14	41.00	32	
1000	1037	Sandstone								15	41.00	33	
										16	40.90	34	
										17	41.90	35	
										18	41.00	36	
										Total: 1022.90' + 4' shoe= 1026.90'			